



**DANGER!**  
Aluminum Conducts Electricity

## ALUMINUM

**300 lbs.**

\*load capacity, user plus tools.  
★ CSA Grade 1 + ANSI Type IA

### EXTENSION LADDER 9800 SERIES INDUSTRIAL - HEAVY DUTY

#### FEATURES

- "D"-shaped rungs
- Quicklatch rung lock
- Full I-Beam siderail
- Mar and impact-resistant end caps
- Heavy Duty slip-resistant safety feet

#### SPECIFICATIONS

- Inside Fly section (16'-24'): 13-1/16" (28'-40'): 13-1/4" (48'): 15-11/16" (60'): 12-5/8"
- Outside Base section: (16'-24'): 17-13/16" (28'-40'): 18" (48'): 20-5/8" (60'): 21-3/4"

MODEL	SIZE (ft)	HEIGHT WHEN FOLDED	MAXIMUM EXTENDED HEIGHT	WEIGHT (lbs)	SHIPPING DIMENSIONS (H x W x L)
9800-16	16	8'	13'	30	5"x18"x8'
9800-20	20	10'	17'	37	5"x18"x10'
9800-24	24	12'	21'	44	5"x18"x12'
9800-28	28	14'	25'	56	5"x18"x14'
9800-32	32	16'	29'	62	5"x18"x16'
9800-36	36	18'	32'	76	6"x18"x18'
9800-40	40	20'	35'	84	6"x18"x20'
9800-48	44	24'	43'	122	6"x21"x24'
9800-60	60	22'	48'	169	6"x22"x22'

\* 60' Triple, middle section outside base: 18-13/16", inside width: 15-5/16".  
\* 48' and 60' sizes are CSA rated for 250 lbs, Grade 1.



## ALUMINUM 250 lbs.

\*load capacity, user plus tools.  
★ CSA Grade 1 + ANSI Type I

### EXTENSION LADDER 7800 SERIES INDUSTRIAL

#### FEATURES

- "D"-shaped rung locks
- Quicklatch rung lock
- Mar and impact resistant end caps
- Heavy Duty slip-resistant safety feet

#### SPECIFICATIONS

- Inside Fly section (16'-40'): 13-15/16"
- Outside Base section: (16'-40'): 17-1/2"

**DANGER!**  
Aluminum Conducts Electricity

MODEL	SIZE (ft)	HEIGHT WHEN FOLDED	MAXIMUM EXTENDED HEIGHT	WEIGHT (lbs)	SHIPPING DIMENSIONS (H x W x L)
7800-16	16	8'	12'	30	6"x18"x8'
7800-20	20	10'	16'	33	6"x18"x10'
7800-24	24	12'	20'	42	6"x18"x12'
7800-28	28	14'	24'	47	6"x18"x14'
7800-32	32	16'	28'	53	6"x18"x16'
7800-36	36	18'	32'	71	6"x18"x18'
7800-40	40	20'	36'	80	6"x18"x20'



\*Wheels sold separately

## ALUMINUM 225 lbs.

\*load capacity, user plus tools.  
★ CSA Grade 2 + ANSI Type II

### EXTENSION LADDER 5800 SERIES MEDIUM DUTY

#### FEATURES

- "D"-shaped rungs
- Quicklatch rung lock
- Mar and impact resistant end caps
- Heavy Duty slip-resistant safety feet

#### SPECIFICATIONS

- Inside Fly section (16'-32'): 14-5/16"
- Outside Base section: (16'-32'): 17-1/8"

**DANGER!**  
Aluminum Conducts Electricity

MODEL	SIZE (ft)	HEIGHT WHEN FOLDED	MAXIMUM EXTENDED HEIGHT	WEIGHT (lbs)	SHIPPING DIMENSIONS (H x W x L)
5816-16	16	8'	12'	24	6"x18"x8'
5820-20	20	10'	16'	30	6"x18"x10'
5824-24	24	12'	20'	35	6"x18"x12'
5828-28	28	14'	24'	45	6"x18"x14'
5832-32	32	16'	28'	52	6"x18"x16'

#### Additional options

##### WHEEL KIT

MODEL: KIT108

SOLD BY: Kit

WEIGHT (lbs): 1.5

SHIPPING: 2"x6"x6"



##### 12" STANDOFF

MODEL: 0715-00

SOLD BY: Pr

WEIGHT (lbs): 1.5

SHIPPING: 3"x14"x20"



##### 'D'-CLEVER' LADDER LEVELLER

MODEL: 0700-00

SOLD BY: Kit

WEIGHT (lbs): 5.3

SHIPPING: 5"x5"x24"

