



FIBERGLASS

375 lbs.

*load capacity, user plus tools.
★ CSA Grade 1 + ANSI Type IAA

EXTENSION LADDER FE4200 SERIES INDUSTRIAL - EXTRA-HEAVY DUTY

FEATURES

- Aluminum plate-to-rail connection riveted to siderail
- "D"-shaped aluminum rung
- Non-conductive fiberglass rails
- Full metal boot
- Quicklatch rung lock
- Outside slide guides
- Mar-resistant rail end caps

SPECIFICATIONS

- Inside Fly section: 13-11/16"
- Outside Base section: 17-3/4"

MODEL	SIZE (ft)	HEIGHT WHEN FOLDED	MAXIMUM EXTENDED HEIGHT	WEIGHT (lbs)	SHIPPING DIMENSIONS (H x W x L)
FE4216HD	16	8'	13'	41	6"x18"x8'
FE4220HD	20	10'	17'	50	6"x18"x10'
FE4224HD	24	12'	21'	58	6"x18"x12'
FE4228HD	28	14'	25'	67	6"x18"x14'



FIBERGLASS

300 lbs.

*load capacity, user plus tools.
★ CSA Grade 1 + ANSI Type IA

EXTENSION LADDER F534 SERIES INDUSTRIAL - HEAVY DUTY

FEATURES

- "D"-shaped aluminum rung swedged to siderails
- Non-conductive fiberglass rails in safety orange
- Quicklatch rung lock
- Outside slide guides
- Mar-resistant rail end caps
- Heavy duty + self-aligning swivel safety feet with steel ice plate

SPECIFICATIONS

- Inside Fly section: (16'-28'): 13-11/16" (32'-40'): 14-5/16"
- Outside Base section: (16'-28'): 17-1/16" (32'-40'): 17-11/16"

MODEL	SIZE (ft)	HEIGHT WHEN FOLDED	MAXIMUM EXTENDED HEIGHT	WEIGHT (lbs)	SHIPPING DIMENSIONS (H x W x L)
F534-16	16	8'	13'	30	6"x18"x8'
F534-20	20	10'	17'	42	6"x18"x10'
F534-24	24	12'	21'	52	6"x18"x12'
F534-28	28	14'	25'	58	6"x18"x14'
F534-32	32	16'	29'	70	6"x19"x16'
F534-36	36	18'	32'	79	6"x19"x18'
F534-40	40	20'	35'	93	6"x19"x20'

* SIZES 36' & 40' ARE MANUFACTURED AND TESTED TO 250LBS (CSA GRADE 1 + ANSI Type I).

Additional options

POLE GRIP

MODEL: 0685-00

SOLD BY: ea

WEIGHT: 3oz

SHIPPING: 1"x2"x25"

CABLE HOOK

MODEL: 0679-00

SOLD BY: Pr

WEIGHT (lbs): 3

SHIPPING: 2"x7"x9"

SWIVEL SAFETY FEET

MODEL: 0682-00

SOLD BY: Pr

WEIGHT (lbs): 2

SHIPPING: 2"x3"x6"