



STEEL

300 lbs.

*load capacity, user plus tools.

ROLLING LADDER

Steel rolling ladders are manufactured to meet or exceed safety standards as set by ANSI (American National Standards Institute) and OSHA (Occupational and Health Administration). Detailed use and maintenance instructions are sent with each ladder.

FEATURES

- ANSI A14.7 & OSHA 1910.29 COMPLIANT
- 14" deep top platform to provide ample working area
- Automatic brake on 2 - 6 step models
- Positive locking system with manual release, standard on 7 - 20 step models and optional on 5 & 6 step models
- Steel construction with powdercoat paint finish
- Perforated tread design to prevent slipping

⚠ DANGER!
Steel Conducts Electricity



MODEL	NUMBER OF STEPS	PLATFORM HEIGHT	WORKING HEIGHT (MAXIMUM)	HAND RAIL	BRAKE TYPE	BASE WIDTH	BASE LENGTH	OVERALL HEIGHT	WEIGHT (lbs)	SHIPPING VOLUME (ft ³)
L02	2	1' 6"	7'	NO	AUTO	26"	21"	1' 6"	33	6.40
L03	3	2' 3"	7' 9"	NO	AUTO	26"	27"	2' 3"	44	11.80
L04	4	3'	8' 6"	NO	AUTO	26"	33"	3'	53	19.80
L03HR	3	2' 3"	7' 9"	YES	AUTO	26"	27"	5' 9"	58	31.30
L04HR	4	3'	8' 6"	YES	AUTO	26"	34"	6' 6"	74	43.00
L05HR	5	3' 9"	9' 3"	YES	AUTO	26"	40"	7' 3"	87	56.40
L06HR	6	4' 6"	10'	YES	AUTO	26"	45"	8'	99	72.00
L05HRL	5	3' 9"	9' 3"	YES	LOCK	26"	40"	7' 3"	105	56.40
L06HRL	6	4' 6"	10'	YES	LOCK	26"	45"	8'	117	72.00
L07HRL	7	5' 3"	10' 9"	YES	LOCK	30"	51"	8' 9"	156	75.80
L08HRL	8	6'	11' 6"	YES	LOCK	30"	57"	9' 6"	169	82.30
L09HRL	9	6' 9"	12' 3"	YES	LOCK	30"	63"	10' 3"	187	88.80
L10HRL	10	7' 6"	13'	YES	LOCK	30"	69"	11'	208	96.60
L11HRL	11	8' 3"	13' 9"	YES	LOCK	30"	74"	11' 9"	222	103.00
L12HRL	12	9'	14' 6"	YES	LOCK	30"	79"	12' 6"	236	109.50
L13HRL	13	9' 9"	15' 3"	YES	LOCK	30"	84"	13' 3"	250	116.70
L14HRL	14	10' 6"	16'	YES	LOCK	30"	90"	14'	270	128.80
L15HRL	15	11' 3"	16' 9"	YES	LOCK	30"	96"	14' 9"	293	130.30
L16HRL	16	12'	17' 9"	YES	LOCK	30"	104"	15' 6"	312	137.40
L18HRL	18	13' 6"	19'	YES	LOCK	30"	114"	17'	336	151.60
L20HRL	20	15'	20' 6"	YES	LOCK	30"	126"	18' 6"	360	166.00

* 18 & 20 step models not tested for ANSI compliancy.