



Wood Stepladder – Series 504

Duty Rating – 300 LBS

Manufacturers Operating Instructions

This product and its use conforms to CSA Z11-12 Portable Ladders.

NOTICE:

A Stepladder is a self-supporting portable ladder, non-adjustable in length, having flat steps and hinged back. The back section consists of either a single ladder or some other supporting device.

This product can be used with planks in a Ladder Type Scaffold (ANSI 10.8 Section 17) setup.

Selection:

- 1) **DANGER! Do not use this product in the vicinity of live electrical wires.**
- 2) The duty rating of this ladder is 300 lbs.
- 3) Select equipment of proper length to reach working height.

Inspection:

- 1) Inspect ladder upon receipt and before each use.
- 2) Make sure all rivets and joints, nuts and bolts are tight and secure.
- 3) Never use a damaged, bent or broken ladder.
- 4) Never make temporary repairs of damaged or missing parts.
- 5) All parts must be in good working order.

Proper Setup:

- 1) Do not set up this product in the vicinity of live electrical wires.
- 2) Place ladder on a firm and level surface. Do not place on a slippery or uneven surface.
- 3) Open ladder and ensure that the spreaders are fully open and in the locked position. Do not use a ladder in a partially closed position.
- 4) Do not place ladder in front of doors that can open toward the ladder.

Proper Climbing and Use:

- 1) Do not use a ladder if you tire easily, are subject to fainting spells, are using medicine or alcohol, or are physically handicapped.
- 2) To protect children, do not leave a ladder setup and unattended.
- 3) Do not stand on the ladder top cap or the first step down from the top.
- 4) Portable ladders are not designed for excessive side loading. Do not overreach. Keep belt buckle between side rails.
- 5) When ascending or descending the ladder, the user shall face the ladder, maintain 3-points of contact and keep a firm grip on the ladder.

Model	Size	Comfortable Reach	Width	Spread	Weight lbs
504-03	3'	7'	18"	23"	10
504-04	4'	8'	20"	30"	14
504-05	5'	9'	21"	35"	18
504-06	6'	10'	23"	42"	21
504-07	7'	11'	24"	46"	25
504-08	8'	12'	26"	51"	28
504-10	10'	14'	29"	62"	35
504-12	12'	16'	33"	74"	42
504-14	14'	18'	36"	87"	56